

EX-armaturer Rino-EX

IP-klass = IP65
Kapslingsklass = I
Temperatur område = -20°C till +40°C
Spänning = 230V
Frekvens = 50-60 Hz
Max kabelarea = 2,5 mm²



EX-armaturer

Lamphållare E27

ZON	GAS			DAMM		
	0	1	2	20	21	22
OK			X		X	X

ATEX Direktiv 94/9/EC
EN 60079-0:2009
EN 60079-15:2010
EN 60079-31:2009

Direktiv 2006/95/EC
EN 60598-1:2008 + A11: 2009
EN 60598-2-1:1989



II 3G Ex nA IIC 145/160/190 °C (T3) Gc
II 2D Ex tb IIIC T 75/85/90 °C Db IP65

Vill du veta mer kontakta oss på:

Mobil Elteknik Sverige AB
Lovisebergsvägen 13, SE-141 32 Huddinge, Sverige
Tel +46 8 449 50 00 Fax +46 8 449 50 01
info@mets.nu www.mets.nu

EX-armaturer Rino-EX



EX-armaturer

Oval armatur

W	Socket	Dimensioner	Artikelnummer
18	E27	199 X 112 mm	ME831072EX
28	E27	226 X 130 mm	ME831172EX
53	E27	295 X 170 mm	ME831272EX

Rund armatur

W	Socket	Dimensioner	Artikelnummer
28	E27	200 X 182 mm	ME830072EX